

P-EOC

POE ETHERNET EXTENDER

KEY FEATURES

- Transfer 60Mbps bi-direction Ethernet signal via coaxial cable, and the transmission distance of Ethernet and power signals up to 300m
- Support IEEE 802.3u 100Base-TX, IEEE802.3 af/at standard
- Low delay rate, less than 0.01ms; Real-time video surveillance
- Plug-and-play, no other software and transfer agreement required
- Built-in splicing slot, with magnet and hanger, unique and integrated design, splicing, desktop and wall-mounted installations available, which suits in all kinds of engineering installation



TECHNICAL SPECIFICATIONS

Power Supply	PoE
Port	BNC, RJ45
Transmission Distance	Ethernet cable: 0~100m Coaxial cable 0 300m(Recommend)
Media	RG 59 or above coaxial cable & Cat5e/6 Ethernet cable
Network Standard	IEEE802.3u 100BASE-TX
Power Indication	Yellow lasting on: Power connection is OK
Data Indication	Green lasting on: Data connection is OK
RJ45 Indication	Green flicker: Data transmission is OK ; Yellow on: PoE is OK
ESD	Contact discharge: Level III; Air discharge: Level III; Execute :
Lightning Protection	IEC61000-4-2 Level III Execute : IEC61000-4-5
Work Temperature	-10°C~55°C
Storage Temperature	-40°C~85°C
Humidity(non-condensing)	0~95%
Size (L x W x H)	113mmX45.5mmX29mm
Material	ABS plastics
Color	Black
Weight	SV piece device 58g IPC piece device 58g

