

# SW4GFP

4 CHANNEL POE SWITCH

## KEY FEATURES

- 2 optical and 2 Ethernet uplink ports, 1 optical port and 1 Ethernet port are Combo ports
- 4x10/100/1000 Mbps adaptive downlink ports, 1~4 ports of PoE switch support IEEE802.3af/at
- Support port(Auto MDI/MDIX)function
- Standard DC port and green terminal port, support power adapter with different connectors and power
- Redundant power design support power hot backup
- Fanless wavy metal shell with heat dissipation design
- Fast installation and easy operation, convenient for wall, din rail and desktop installation



## TECHNICAL SPECIFICATIONS

Downstream Ports	4* 10/100/1000Base-T
Uplink Ports	2*1000Mbps SFP Port and 2*10/100/1000Base-T
Network Standard	IEEE802.3, IEEE802.3u, IEEE802.3a, IEEE802.3z, IEEE802.3x
Switch Capacity	17.5Gbps
Throughput	10.4Mpps
Switch Processing Scheme	Store and Forward
Memory Buffer	1Mbit
MAC Table	8K
PoE Standard	802.3af/at
PsE Type	End-span
Power Pin Assignment	1/2(+), 3/6(-)
PoE Power Output	44~57V DC , 60 watts max
PoE Budge	60 watts max (Can be ordered 120W)
Lightning protection	6KV Execute : IEC61000-4-5
ESD	6KV Contact discharge 8KV Air discharge Execute : IEC61000-4-2
Power Supply	DC 48~57V
Power Dissipation	<6W
Work temperature	-40°C~75°C
Storage temperature	-40°C~85°C
Humidity(Non-condensin)	5%-95%
Dimension (LxWxH)	163mmx110mmx46mm
Weight	530g
Regulator	CE、FCC、ROHS

## TECHNICAL DIAGRAM

